







"...the only port of call you'll ever need..."

Emergency Towing System Equipment List for After Ship



Equipment Listing

Covering Models: LMS-102 & LMS-202

Equipment	Model: LMS-102	Model: LMS-202
Storage Drum 	Drum Capacity: <ul style="list-style-type: none"> - For Towing Pennant - Dia. 62mm with groove for the Anchor Socket 	Drum Capacity: <ul style="list-style-type: none"> - For Towing Pennant - Dia. 82mm with groove for the Anchor Socket
Retrieval Wire 	<ul style="list-style-type: none"> - Wire Rope Dia. 12mm x 7m, 6 x 37 Galvanised 	<ul style="list-style-type: none"> - Wire Rope Dia. 16mm x 9.5m, 6 x 37 Galvanised
Towing Pennant 	<ul style="list-style-type: none"> - Wire Rope Dia. 62mm x 80m, 6 x 37 IWRC - With closed splintered sockets & anchor socket - Working Load: 1000 KN - Min. Breaking Load: 2000 KN 	<ul style="list-style-type: none"> - Wire Rope Dia. 82mm x 100m, 6 x 47 IWRC - With closed splintered sockets & anchor socket - Working Load: 2000 KN - Min. Breaking Load: 4000 KN
Strongpoint Fairlead 	Towing Bracket: <ul style="list-style-type: none"> - Steel plate, weld construction, integrated with fairlead - Working Load: 1000 KN - Min. Breaking Load: 2000 KN 	Towing Bracket: <ul style="list-style-type: none"> - Steel plate, weld construction, integrated with fairlead - Working Load: 2000 KN - Min. Breaking Load: 4000 KN
Messenger Line 	<ul style="list-style-type: none"> - Nylon rope Dia. 40mm x 100m - Min. Breaking load: 30 Tons 	<ul style="list-style-type: none"> - Nylon rope Dia. 44mm x 100m - Min. Breaking load: 36 Tons
Withdrawal Line 	<ul style="list-style-type: none"> - Wire rope Dia. 12mm x 90m. 6 x 37 Galvanised 	<ul style="list-style-type: none"> - Wire rope Dia. 12mm x 90m. 6 x 37 Galvanised
Pick-Up Line 	<ul style="list-style-type: none"> - P.P. Rope Dia. 20mm x 30m 	<ul style="list-style-type: none"> - P.P. Rope Dia. 20mm x 30m
Buoy 	Towing Bracket: <ul style="list-style-type: none"> - Steel plate, weld construction, integrated with fairlead - Working Load: 1000 KN - Min. Breaking Load: 2000 KN 	Towing Bracket: <ul style="list-style-type: none"> - Steel plate, weld construction, integrated with fairlead - Working Load: 2000 KN - Min. Breaking Load: 4000 KN
Container 	For Pick-Up Gear <ul style="list-style-type: none"> - Contains the Pick-Up Gear - Dimensions: 1m x 0.7m x 1m 	For Pick-Up Gear <ul style="list-style-type: none"> - Contains the Pick-Up Gear - Dimensions: 1m x 0.75m x 1m
** Pedestal Roller 	<ul style="list-style-type: none"> - Dia. 300mm with Conical base 	<ul style="list-style-type: none"> - Dia. 350mm with Conical base
Note: <ol style="list-style-type: none"> 1) with Class Approval & Certificate 2) The Pick-Up Gear & Buoys have to be manually deployed by one of the crew members. 		

** Optional.

Please e-mail us at sales@liftingandmarine.com with your enquiry

www.liftingandmarine.com