








"...the only port of call you'll ever need..."

Emergency Towing System Equipment List for Forward Ship



Equipment Listing

Covering Models: **LMS-302, LMS-402 & LMS-403**

Equipment	Model: LMS-302	Model: LMS-402
Smit Bracket 	<ul style="list-style-type: none"> - For dia. 54mm Chafe Chain (Grade 3) - Safe Working Load: 1000 KN - Min. Breaking Load: 2000 KN 	<ul style="list-style-type: none"> - For dia. 76mm Chafe Chain (Grade 3) - Safe Working Load: 2000 KN - Min. Breaking Load: 4000 KN
Panama Chock 	<ul style="list-style-type: none"> - Bulwark or deck mounted - Nominal size: 600 x 450mm 	<ul style="list-style-type: none"> - Bulwark or deck mounted - Nominal size: 600 x 450mm
Chafe Chain	<ul style="list-style-type: none"> - Dia. 54mm x 7m length (Grade 3) - Safe Working Load: 1000 KN - Min. Breaking Load: 2000 KN 	<ul style="list-style-type: none"> - Dia. 76mm x 7m length (Grade 3) - Safe Working Load: 2000 KN - Min. Breaking Load: 4000 KN
Fairlead Roller 	<ul style="list-style-type: none"> - Dia. 350mm with Conical base 	<ul style="list-style-type: none"> - Dia. 400mm with Conical Base
**Towing Shackle 	<ul style="list-style-type: none"> - Nominal size: 64mm - Safe Working Load: 1000 KN - Min. Breaking Load: 2000 KN 	<ul style="list-style-type: none"> - Nominal size: 76mm - Safe Working Load: 2000 KN - Min. Breaking Load: 4000 KN
**Towing Pennant 	<ul style="list-style-type: none"> - Wire Rope Dia. 58mm x 80m, 6 x 37 IWRC - With close speltered sockets - Working Load: 1000 KN - Min. Breaking Load: 2000 KN 	<ul style="list-style-type: none"> - Wire Rope Dia. 76mm x 100m, 6 x 41 IWRC - With close speltered sockets - Working Load: 2000 KN - Min. Breaking Load: 4000 KN

Equipment Chain Cable Stopper 	Model: LMS-403 <ul style="list-style-type: none"> - For dia. 76mm Chafe Chain (Grade 3) - Safe Working Load: 2000 KN - Min. Breaking Load: 4000 KN - Plinth for stopper on request
Panama Chock Chafe Chain	<ul style="list-style-type: none"> - Bulwark or deck mounted, Nominal Size: 600 x 450mm - Dia. 76mm x 8m Length (Grade 3), Safe Working Load: 2000 KN, Min. Breaking Load: 4000 KN
Fairlead Roller **Towing Shackle	<ul style="list-style-type: none"> - Dia. 400mm with conical base - Nominal Size: 76mm, Safe Working Load: 2000 KN, Min. Breaking Load: 4000 KN
**Towing Pennant	<ul style="list-style-type: none"> - Wire Rope Dia. 76mm x 100m, 6 x 41 IWRC, Working Load: 2000 KN, Min. Breaking Load: 4000 KN Includes Closed Speltered Sockets

** Optional.

Note: Length of the Chafe Chain can be as requested.

Please e-mail us at enquiries@liftingandmarine.com with your enquiry

www.liftingandmarine.com