



"...the only port of call you'll ever need..."

## Escort / Pull Back Towing System (OCIMF)



LMS provides escort pull back system options for both Tug and Tanker operators. Please refer to the equipment list below for more information..

To receive a competitive quotation please send us your email enquiry to us today at [enquires@liftingandmarine.com](mailto:enquires@liftingandmarine.com)



### For Tug Owner

- Towing lines with eyes. at least 1800 mm in length.



### For Tanker Owner

#### Equipment

#### 20,000 to 50,000 DWT

#### > 50,000 DWT

#### Fairlead - Chock

- EU Type, Deck Mounted
- Nominal size: 500 x 400mm
- Safe Working Load: 1000 KN
- Min. Breaking Load: 2000 KN

- EU Type, Deck Mounted
- Nominal size: 600 x 450mm
- Safe Working Load: 2000 KN
- Min. Breaking Load: 4000 KN

#### Deck Bollard

- Double Bitt
- Nominal size: 400mm
- For Rope BL: 64 Ton
- Figure of Eight Belayed: 32 Tons

- Double Bitt
- Nominal size: 500mm
- For Rope BL: 100 Ton
- Figure of Eight Belayed: 50 Tons

#### Strongpoint Bollard

- Model: DB-138 Double Bitt
- Nominal size: 500mm
- Safe Working Load: 1000 KN
- Min. Breaking Load: 2000 KN
- For Single Eye Towing Line or Grommet

- Model: SB-138 Single Bitt
- Nominal size: 630mm
- Safe Working Load: 2000 KN
- Min. Breaking Load: 4000 KN
- For Single Eye Towing Line or Grommet

- Under Deck Stiffening as request.
- With Class Type Approval Certificate

Please e-mail us at [enquires@liftingandmarine.com](mailto:enquires@liftingandmarine.com) with your enquiry

[www.liftingandmarine.com](http://www.liftingandmarine.com)