

* Denotes fitted with Phosphor Bronze Bush Proof Load 2 x Headload 601H Model available with safety catch



		Wire					Wire		
Sheave Dia		Rope	Headload Tonne		Sheave Dia		Rope	Headload Tonne	
mm	inch	Dia mm	5:1 FOS	4:1 FOS	mm	inch	Dia mm	5:1 FOS	4:1 FOS
* 76	3	7-9	1.6	2	203	8	20-22	12	15
* 114	4 1/2	10 - 12	3.2	4	254	10	24-26	12	15
* 152	6	12 - 14	3.2	4	305	12	24-26	12	15
* 203	8	10 - 12	3.2	4	357	14	24-26	12	15
152	6	20-22	6.4	8	406	16	24-26	12	15
203	8	20-22	6.4	8	458	18	24-26	12	15
254	10	20-22	6.4	8	203	8	28-30	17.5	22
305	12	20-22	6.4	8	254	10	28-30	17.6	22
357	14	20-22	6.4	8	305	12	28-30	17.6	22
406	16	20-22	6.4	8	357	14	28-30	17.6	22
458	18	20-22	6.4	8	406	16	28-30	17.6	22
152	6	20-22	9.6	12	458	18	28-30	17.6	22
203	8	20-22	9.6	12	* 203	8	28-30	24	30
254	10	20-22	9.6	12	* 254	10	28-30	24	30
305	12	20-22	9.6	12	305	12	28-30	24	30
357	14	20-22	9.6	12	357	14	28-30	24	30
406	16	20-22	9.6	12	406	16	32-35	24	30
458	18	20-22	9.6	12	458	18	32-35	24	30
152	6	20-22	12	15					

www.liftingandmarine.com